





UFRX/ALS PCO

PURIFICATION AND FILTER UNITS WITH PHOTOCATALYSIS TECHNOLOGY FOR INDOOR AIR AND SURFACES DISINFECTION



- BUILT-IN PHOTOCATALYST DEVICE
- AIR PRE-FILTERING STAGE
- NEGATIVE AND POSITIVE IONISATION
- EASY ACCESS FOR MAINTENANCE



FILTRATION STAGES






UFRX/ALS PCO

UFRX/ALS PCO air purification units are designed for disinfecting, cleaning, eliminating odours and purifying air in **high occupancy areas that have stringent soundproofing and versatility requirements.**

ACTIVE DISINFECTING TECHNOLOGY




PCO™ technology (Photocatalytic Oxidation) is a powerful tool that is used for purifying air and nearby surfaces, by accelerating the natural decomposition of organic matter through photocatalysis.

Additionally, our equipment has built-in modules with **positive and negative ionisation technology**, which improve their purifying efficacy against ultra-fine dust and odours.


HOW DOES IT WORK?

PCO technology uses a UVC ultraviolet light source to react with a titanium dioxide catalyst in the presence of humidity/water vapour to create hydroxyl radicals (OH) and hydrogen peroxide (H₂O₂), which inactivate airborne microorganisms and harmful chemical substances circulating in the air.

These devices use PCO technology, together with **positive and negative ionisation**, to gather suspended particulate matter, which has not been collected by filters, and make it harmless.



Positive and negative ionisation of particles





APPLICATIONS

Purifying air by disinfecting it using **PCO technology is ideal for premises where people are continuously entering and exiting.** These premises require a speedy, high efficiency disinfection due to the high rate of pollutants that may be circulating.


PCO technology is also suitable for use at locations where there is a need to disinfect large material surfaces through the air.

RECOMMENDED FOR

- Hospitals
- Food industry
- Businesses
- Offices
- Waiting rooms
- Clean rooms
- Libraries

BENEFITS

- Eliminates germs, viruses, mould and bacteria
- Does not pollute
- Reduces odours
- Helps alleviate allergies and control asthma
- Effective against all organic pollutants
- Eliminates ultra-fine dust and animal hair






LOW NOISE LEVEL

The 25 mm acoustic casing is made of high-quality insulating material, ensuring that this unit operates at low noise levels.



DURABILITY

These units are made from prefinished sheet metal and aluminium profiles, providing them with excellent corrosion resistance, increasing their service life.



PHOTOCATALYST DEVICE

Device with PCO technology and ambient air positive and negative ionisation technology. Designed to improve indoor air quality as well as disinfecting air and nearby surfaces to eliminate germs, viruses and bacteria.



EASY TO INSTALL AND MAINTAIN

The inside of the unit can be quickly accessed through the inspection panel for cleaning and for filter replacement or to use the UVC ultraviolet light if required.



PRODUCTS WITH CERTIFIED PCO TECHNOLOGY THAT ARE 100% EFFECTIVE IN 10 MINUTES AGAINST MENOGENOVIRUS

The efficacy of PCO technology has been proven in a laboratory certified by ENAC and APPLUS+ in accordance with standard EN 14476 for the evaluation of virucidal activity in the medical area for antiseptic and disinfectant tests.

Mengovirus is a microorganism of the same family as the SARS-CoV-2, which causes COVID-19.



UFRX/ALS PCO

Air purification units with technology based on photocatalysis



Filtration, disinfection and air purification units with photocatalysis technology, especially designed for disinfecting and cleaning indoor air and nearby surfaces.

Characteristics:

- Aluminium profile structure.
- Covers made from prefinished sheet, with high quality, 25 mm thick acoustic insulation.
- Backward-curved impeller.
- Built-in photocatalyst device with negative and positive ionisation.
- Filtration stages: F7+F9.
- Inspection cover for maintenance and filter replacement.
- Effective for up to 40 linear metres of ducting.
- Belt-driven.
- Cable entry gland.

Motor:

- IE3 efficiency motors.
- Class F motors with ball bearings and IP55 protection.
- Three-phase 230/400 V 50 Hz (up to 4 kW) and 400/690 V 50 Hz (powers higher than 4 kW).
- Carried air temperature range: -20 °C to +60 °C.


Finish:

- Aluminium profile and prefinished sheet, with 25 mm thick double-wall thermal and acoustic insulation panels.

On request:

- Circular outlet.

Order code



Characteristics of the filters

STANDARD FILTERS

	EN 779		EN 1822		ISO 16890			
	F7	F9	ISO ePM ₁	ISO ePM _{2.5}	ISO ePM ₁₀	ISO COARSE		
F7	90%	-	>50%	>65-95%	>85%	-		
F9	95%	-	>80%	>95%	>95%	-		

Technical characteristics


Model	Speed (r/min)	Maximum admissible current (A)			Installed power (kW)	Maximum flow rate (m ³ /h)	Sound pressure level dB(A)	Air temperature (°C)		Approx. weight (kg)	According ErP
		230 V	400 V	690 V				min.	max.		
UFRX/ALS PCO-315-2 IE3	2100	5.34	3.07		1.50	6460	75	-20	+60	87	2018
UFRX/ALS PCO-315-3 IE3	2350	7.70	4.43		2.20	6460	75	-20	+60	92	2018
UFRX/ALS PCO-355-3 IE3	1930	7.93	4.56		2.20	8980	78	-20	+60	118	2018
UFRX/ALS PCO-355-4 IE3	2180	10.70	6.15		3.00	8980	78	-20	+60	124	2018
UFRX/ALS PCO-400-4 IE3	1820	10.70	6.15		3.00	10370	75	-20	+60	135	2018
UFRX/ALS PCO-400-5.5 IE3	2000	13.90	8.00		4.00	10370	75	-20	+60	147	2018
UFRX/ALS PCO-500-5.5 IE3	1370	13.90	8.00		4.00	15030	73	-20	+60	188	2018
UFRX/ALS PCO-500-7.5 IE3	1510	10.30	5.97		5.50	15030	73	-20	+60	214	2018
UFRX/ALS PCO-630-7.5 IE3	1020	11.20	6.49		5.50	23330	72	-20	+60	320	2018
UFRX/ALS PCO-630-10 IE3	1135	14.80	8.58		7.50	23330	72	-20	+60	340	2018



Erp. (Energy Related Products)

Information on Directive 2009/125/EC can be downloaded from the SODECA website or the QuickFan selector programme


Dimensions mm



MODEL	A	A1	B	B1	C	D1	D2	E1	E2	L1	L2	H1	H2
UFRX/ALS PCO-315	1867	1998	855	895	855	910	795	795	135	405	580	815	1168
UFRX/ALS PCO-355	2005	2125	1000	1040	1000	1040	940	940	210	455	585	960	2095
UFRX/ALS PCO-400	2130	2250	1195	1235	1195	1245	1115	1115	300	510	580	1155	2220
UFRX/ALS PCO-500	2500	2620	1450	1490	1450	1520	1370	1370	175	640	1100	1410	2590
UFRX/ALS PCO-630	2605	2725	1670	1710	1670	1740	1590	1590	140	805	1390	1630	2695


Characteristic curves

UFRX/ALS PCO-315




Characteristic curves


UFRX/ALS PCO-355




UFRX/ALS PCO-400



Characteristic curves



Characteristic curves



Accessories



INT



MTP



VSD3/A-RFT



AET



VIS



TEJ



HEADQUARTERS
Sodeca, S.L.U.

Pol. Ind. La Barricona
Carrer del Metall, 2
E-17500 Ripoll
Girona, SPAIN
Tel. +34 93 852 91 11
Fax +34 93 852 90 42
General sales: comercial@sodeca.com
Export sales: ventilation@sodeca.com

PRODUCTION PLANT
Sodeca, S.L.U.

Ctra. de Berga, km 0,7
E-08580 Sant Quirze de Besora
Barcelona, SPAIN
Tel. +34 93 852 91 11
Fax +34 93 852 90 42
General sales: comercial@sodeca.com
Export sales: ventilation@sodeca.com

SODECA Group

EUROPE

FINLAND
Sodeca Finland, Oy

HUITTINEN
Sales and Warehouse
Mr. Kai Yli-Sipilä
Metsälinnankatu 26
FI-32700 Huittinen
Tel. + 358 400 320 125
orders.finland@sodeca.com

HELSINKI
Smoke Control Solutions
Mr. Antti Kontkanen
Vilppulantie 9C
FI-00700 Helsinki
Tel. +358 400 237 434
akontkanen@sodeca.com

HYVINKÄÄ
Industrial Applications
Mr. Jaakko Tomperi
Niinistökatu 12
FI-05800 Hyvinkää
Tel. +358 451 651 333
jtomperi@sodeca.com

ITALIA
Marelli Ventilazione, S.R.L.

Viale del Lavoro, 28
37036 San Martino B.A.
(VR), ITALY
Tel. +39 045 87 80 140
vendite@sodeca.com

PORTUGAL
Sodeca Portugal, Unip. Lda.

PORTO
Rua Vello Salgado
1120/1138
4450-801 Leça de Palmeira
Tel. +351 229 991 100
geral@sodeca.pt

LISBOA
Pq. Emp. da Granja Pav. 29
2625-607 Vialonga
Tel. +351 219 748 491
geral@sodeca.pt

ALGARVE
Rua da Alegria, 33
8200-569 Ferreiras
Tel. +351 289 092 586
geral@sodeca.pt

UNITED KINGDOM
Sodeca Fans UK, Ltd.

Mr. Mark Newcombe
Tamworth Enterprise Centre
Philip Dix House, Corporation
Street, Tamworth, B79 7DN
UNITED KINGDOM
Tel. +44 (0) 1827 216 109
sales@sodeca.co.uk

AMERICA

CHILE
Sodeca Ventiladores, SpA.

Sra. Sofía Ormazábal
Santa Bernardita 12.005
(Esquina con Puerta Sur)
Bodegas 24 a 26,
San Bernardo, Santiago, CHILE
Tel. +56 22 840 5582
ventas.chile@sodeca.com

COLOMBIA
Sodeca Latam, S.A.S.

Sra. Luisa Stella Prieto
Calle7 No. 13 A-44
Manzana 4 Lote1, Montana
Mosquera, Cundinamarca
Bogotá, COLOMBIA
Tel. +57 1 756 4213
ventascolombia@sodeca.co

PERU
Sodeca Perú, S.A.C.

Sr. Jose Luis Jiménez
C/ Mariscal Jose Luis de
Orbegoso 331. Urb. El pino,
15022, San Luis. Lima, PERU
Tel. +51 1 326 24 24
Cel. +51 994671594
comercial@sodeca.pe

RUSSIA

RUSSIA
Sodeca, L.L.C.

Mr. Stanislav Alifanov
Severnoye Shosse, 10 room 201
Business Park Plaza Ramstars
140105 Ramenskoye,
Moscow region, RUSSIA
Tel. +7 495 955 90 50
alifanov@sodeca.com



www.sodeca.com

