

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
CB-820-4T	B	Total	VFD ikke nødvendig	1.00	46.2	55.0	0.412	1870	367	1352
CB-820-4M	B	Total	VFD ikke nødvendig	1.00	44.7	53.3	0.427	1870	367	1371
CB-1428-4T IE3	A	Statisk	VFD ikke nødvendig	1.01	42.4	50.4	0.547	1386	602	1452
CB-1428-6T	A	Statisk	VFD ikke nødvendig	1.00	34.5	45.9	0.160	1086	183	962
CB-1733-4T-1.5 IE3	A	Statisk	VFD ikke nødvendig	1.01	49.4	55.4	1.108	2700	729	1461
CB-1733-4T-2 IE3	A	Statisk	VFD ikke nødvendig	1.01	44.0	49.5	1.355	2913	736	1453
CB-1733-6T IE3	A	Statisk	VFD ikke nødvendig	1.00	38.9	47.7	0.411	1834	314	974
CB-2240-6T IE3	A	Statisk	VFD ikke nødvendig	1.00	42.9	49.6	0.871	2857	471	983