

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

ηe [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOLINEO/EW-100				ErP eksklus. Pe < 125 W						
NEOLINEO/EW-125				ErP eksklus. Pe < 125 W						
NEOLINEO/EW-150				ErP eksklus. Pe < 125 W						
NEOLINEO/EW-160				ErP eksklus. Pe < 125 W						
NEOLINEO/EW-200	A	Statisk	VFD innebygd i viften	1.00	46.3	57.5	0.168	780	360	2950
NEOLINEO/EW-250	A	Statisk	VFD innebygd i viften	1.00	48.3	58.4	0.249	981	441	2950